

PRO 1000

Fluid-Applied Membrane Dampproofing

Product Data Sheet

PRODUCT NAME

PRO 1000

MANUFACTURER

Polyguard Products, Inc.
Ennis, TX 75119
(214) 515-5000
www.polyguardproducts.com

PRODUCT DESCRIPTION

BASIC USES

PRO 1000 is a patented, single component, cold-applied, non-elastomeric, non-breathable, thermoplastic membrane. It dries to a UV resistant and tough re-coatable hard coat protective film that stops water passage through a substrate. This feature allows for durable and maintainable protection from rain and melting snow in the area between grade and the exterior finish. It is designed for use in positive side hydrostatic pressure applications. It can also be used as a vapor impermeable coating on the inside of a below-grade wall when the outside of the wall has either been water or damp proofed with this or other Polyguard material.

PRO 1000 is designed for application over poured concrete, precast concrete and concrete masonry below-grade walls.

COMPOSITION & MATERIALS

PRO 1000 is solvent based with a VOC content of <600g/l. Hard glossy finish that can be recoated.

For designers wanting maximum protection, Proban® added at the factory delivers additional contact mold-inhibiting properties to the waterproofing system.

Available accessory products include: Detail Sealant PW™ and Crack Injection materials.

TECHNICAL DATA

See physical properties table

INSTALLATION

SURFACE PREPARATION

Poured concrete Walls:

Fill honeycombs with non-shrinking Portland cement grout. Remove form ties from both sides of the wall. On the side of the wall that will be coated, fill tie depression irregularities flush using Detail Sealant PW or non-shrinking Portland cement grout.

Concrete Masonry Units (CMU):

Do not use PRO 1000 over CMU units containing integral moisture repellants without prior compatibility testing. Tool and brush mortar joints. Fill surface voids in CMU's

with non-shrinking Portland cement grout, or Detail Sealant PW. Submit control joint waterproofing design to Polyguard Products, Inc. for approval prior to commencing work.

PRIMING

No primer necessary.

MEMBRANE APPLICATION

Apply PRO 1000 in ambient temperatures between -20°F (29°C) and 120°F (49°C). For optimum results the material temperature should be at a minimum 50°F (10°C) prior to application. Lower temperatures decrease material flow properties.

Apply PRO 1000 over poured concrete walls and footings and CMU walls that have cured a minimum of 3 days, have a minimum 175 PSI pull-off strength per ASTM D4541, are dry to touch, are clean and frost free. In conditions where a wall has been under water, do not proceed until the area has been drained and the concrete has dried to the touch.

Apply PRO 1000 in one or more coats over poured concrete at a combined rate of 40 ft² per gallon (40 wet mils). Coverage rates over CMU's are dependent on the tightness of the surface profile.

Membrane blistering can be avoided by applying PRO 1000 during a wall exposure in its daily cooling cycle. Applications on walls experiencing daily warming due to direct sunlight should be executed in 20 mil applications, allowing each coat to dry before applying the next coat. Applications can be made by brush, roller or airless sprayer having a minimum stall pressure of 4000 PSI and using a 0.036 to 0.039 -inch reversible tip.

INSPECTION

Inspect coated surfaces for complete and continuous coverage at the desired mil thickness. Correct deficiencies by applying additional material.

MEMBRANE REPAIR

Repair damage or UV overexposure prior to installation of protection materials by cleaning the damage and applying additional material to specification.

PROTECTION

Protect above grade areas of PRO 1000 from UV exposure by recoating exposed above grade areas every 5-7 years. For a successful painting overcoat, use a bonding additive equal to the properties of Wil-Bond Liquid Surface Preparation.

Protect below grade areas using: Lowflow™ Protection and Drainage Mat; Polyflow® 10 or 10P sheet molded drain or; Polyflow® 15 or 15P sheet molded drain. Drain

these products to daylight or operational sump. Securely adhere one of the listed products over the face of PRO1000 that has dried a minimum of 3 days. Adhere protection using Quick Grip Adhesive.

Protect and drain PRO 1000 over an area from a minimum of 4-inches below the top of interior slab to 6-inches below the top of grade.

BACKFILL

After passing inspection of the completed drainage/protection system, backfill using clean fill material. Place backfill materials to within 2 feet of finish grade. Backfill the remaining area with native soils. Shape the grade to drain away from the structure.

STORAGE

Drums and pails should be stored outside, out of direct sunlight, in temperatures between -20°F (29°C) and 110°F (43°C) and on a stable surface. Indoor storage requires a fire sprinkler system. Follow local governing requirements.

SAFETY

SDS sheets for all Polyguard products can be obtained at our website www.polyguardproducts.com. Call Polyguard Products, Inc. at 214.515.5000 with questions.

WARRANTY

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product are beyond our control; such as weather, workmanship, equipment utilized and prior condition of the substrate. We will replace at no charge product proved to be defective within twelve (12) months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. A five (5) year material or system warranty may be available upon request. Contact Polyguard Products, Inc. for further details.

TECHNICAL SERVICES

Technical assistance, information and Polyguard's products are available through a nationwide network of distributors and architectural representatives, or contact Polyguard Products, Inc.
P.O. Box 755, Ennis, TX 75120-0755
Sales: (615) 217-6061 • Tech Support: (214) 515-5000 • Fax: (615) 691-5500
Email: archtech@polyguardproducts.com
Website: www.polyguardproducts.com

PROPERTY	TEST METHOD	TYPICAL VALUE
COLOR		Available in Gray or Beige
ADHESION	ASTM C 836-89a	Exceeds
ADHESION	ASTM D 4541	100+ PSI
PERMEANCE	ASTM E 96 Method B	0.45 perm
RESISTANCE TO HYDROSTATIC HEAD	Water Column	100ft.
WATER ABSORPTION	ASTM D 95	< 1% weight
METABOLITES	GSA-PBS 07115	Unaffected
WATER PENETRATION and LEAKAGE THROUGH MASONRY	ASTM E 154	No Penetration or Leakage
CATEGORY 1 40 C.F.R.§59401 "WATERPROOFING SEALERS AND TREATMENTS"		<600 g/l

PACKAGING	PART NUMBER	UNIT SIZE
PRO 1000	PWPRO1000 GRAY 05	5 gallon pail
<i>Proban® mold inhibitor can be added at the factory.</i>	PWPRO1000 GRAY 55	55 gallon drum
PRO 1000 Accessories:		
DETAIL SEALANT PW™	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn
DETAIL SEALANT PW™	DETAIL SEALANT PW – 3 GAL	3 gallon pail
LOWFLOW™	LOWF	4' x 200' roll
POLYFLOW® 10	POLYFLOW10	4' x 50' roll
POLYFLOW® 10P	POLYFLOW10P	4' x 50' roll
POLYFLOW® 15	POLYFLOW15	4' x 50' roll
POLYFLOW® 15P	POLYFLOW15P	4' x 50' roll
TOTALFLOW™	TOTAL FLOW	24" x 50' roll
TOTALFLOW™ END OUTLET (4")	OUTLET4-UNIV	N/A
TOTALFLOW™ TEE OUTLET (4")	TEE4-UNIV	N/A
QUICK GRIP SPRAY ADHESIVE	PWQGADH30	30# canister

P.O. Box 755
Ennis, TX 75120
PH: (214) 515-5000
FX: (972) 875-9425

The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.

