



Division of Sierra Corporation
ISO 9001:2008 Certified

TK-2012 KWIK KLEAN STRIPPER/CLEANER/DEGREASER

Technical Data

1. PRODUCT NAME TK-2012 KWIK KLEAN

2. MANUFACTURER
TK PRODUCTS
DIVISION OF SIERRA CORPORATION
11400 West 47th Street
Minnetonka, MN 55343
952-938-7223
952-938-8084 (FAX)
e-mail: tksales@tkproduct.com
Website: <http://www.tkproduct.com>

3. PRODUCT DESCRIPTION
TK-2012 KWIK KLEAN is designed to remove acrylic resin based curing and sealing compounds, as well as most forms of graffiti from concrete surfaces—either horizontal or vertical. TK-2012 KWIK KLEAN will successfully remove most carpet and vinyl floor adhesives, many forms of paint (i.e. dry fogs, latex, acrylics, etc.) and may be used as a stain and dirt remover for concrete floors and driveways.

4. TECHNICAL DATA
Composition and Materials:
A blend of limonene, ester and ketone.

Flash Point:	115°F
VOC:	8.14 lb/gallon
Color:	Clear
Viscosity @ 77°F:	15 - 20 seconds Zahn #2

Effective on these substances:

Epoxies:	No
Urethane:	No
Latex Paint:	Yes
Curing Compounds:	Yes
Acrylic Sealers:	Yes
Grease/Oil:	Yes
Spray Paint:	Yes
Graffiti:	Yes
Silicones:	No
Adhesives:	Some

5. APPLICATION INSTRUCTIONS
Preparation:
For proper application, the surface must be dry and free from extreme amounts of dirt or contamination. If the surface is extremely dirty, power wash and allow to dry thoroughly before application.

Mixing:
TK-2012 KWIK KLEAN is supplied ready to use and requires no mixing or stirring.

Application:
Apply TK-2012 KWIK KLEAN by spray, brush or roller at a rate of 200-300 ft²/gallon.
KWIK KLEAN is most effective when flooded onto the surface and kept wet for 5-10 minutes. If stains have not started to dissolve or run off the surface within this time, reapply and use a stiff bristle brush or broom to aid in removal. Once clean, wipe with a cloth and rinse the area with soap and clean water.

To remove curing and sealing compounds, apply TK-2012 KWIK KLEAN to the surface and allow to sit for 15-30 minutes. The compound may then be removed with a scraper. Lastly, the surface should be pressure washed to remove any remaining residue or contamination. Place residue in a closed metal container to avoid spontaneous combustion and avoid spontaneous combustion during temporary storage by soaking soiled rags and waste in a closed water-filled metal container immediately after use.

Coverage:
Coverage rates will be dependent upon the porosity of the concrete. A test patch should always be applied to determine coverage rate and compatibility with substrate and color.
Apply at 200 – 300 sq. ft. per gallon.

Clean Up:
Clean tools and spills immediately with warm soapy water.

Spills and Leaks:
Eliminate all sources of ignition, flares, and flames including pilot lights. Stop spill at the source. Material is absorbed by sand, clay, earth and floor absorbent.

Safety Information:
Inhalation: Excessive and prolonged inhalation may result in headache, nausea, and eye and lung irritation.
Ingestion: Health risks and symptoms include gastrointestinal irritation, nausea, vomiting and diarrhea. Over exposure of this material has been suggested as a cause of cardiac abnormalities.

Precautions:
Keep away from fire, sparks or flames as well as residual vapors and residue. Do not cut, puncture or weld on or near this container for any purpose until commercially cleaned. If exposure limits of product or any component is exceeded, a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental controls. OSHA regulations also permit other NIOSH/MSHA respirators under specified conditions.

6. AVAILABILITY
TK-2012 KWIK KLEAN is available through TK distributors. Contact the TK office for your nearest distributor.
Packaged in 55-gallon drums, 5-gallon pails, 1-gallon cans, and quart containers.

7. LIMITED WARRANTY
TK Products, a division of The Sierra Corporation, warrants that its products conform to their label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of its products by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. **SHOULD ANY OF ITS PRODUCTS FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCTS OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THE PRODUCTS OF TK PRODUCTS TO PERFORM**

TK-2012 KWIK KLEAN
Stripper/Cleaner/Degreaser

TK
PRODUCTS



TK
PRODUCTS

TK-2012 KWIK KLEAN
Stripper/Cleaner/Degreaser

AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing. See also TK PRODUCTS DISCLAIMER section below.

8. TECHNICAL SERVICES

The TK office offers assistance with specifications, performance test data and field services.

9. FILING SYSTEMS

Information Handling Services

PO BOX 1213

Englewood, CO 80150

Information Marketing Services

13271 Northend

Oak Park, MI 48237

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field test by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also LIMITED WARRANTY (Section 7) above.

FOR INDUSTRIAL USE ONLY

10/12