

Polyguard® Airlok Flex® VP

Fluid-Applied / Air Barrier Membrane

MATERIALS LIST

ABOVE-GRADE FLUID-APPLIED AIR BARRIER

Polyguard Airlok Flex® VP

Airlok Flex® VP is a fluid-applied air barrier coating and is used over CMU, gypsum and wood sheathing. It can be applied in temperatures of 40°F (4°C) and rising, at an application thickness of 32 mils wet, and a coverage rate of 50 SF per gallon (Gypsum board is the standard for coverage, though coverage is inversely related to texture). The VOC content is <50 g/l, and a UV resistance of up to 1 year.

Polyguard Airlok Flex® VP	Part Number	Unit Size	Units/pallet	Wt/unit
<i>Proban® mold inhibitor can be added at the factory to Airlok Flex® VP</i>	PWALFLEXVP05	5 gallon pail	36 pails/pallet	58#/pail
	PWALFLEXVP50	50 gallon drum	4 dr/pallet	550#/dr
Polyguard Airlok Flex® VP Accessories:	Part Number	Unit Size	Units/pallet	Wt/unit
Detail Sealant PW™ 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Detail Sealant PW™ 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3 gallon pail	36 pails/pallet	37#/pail
400 Flashing - 40 mil (sizes available: 4", 6", 9", 12", 16", 24")	varies/size	75' roll	varies/size	varies/size
400 Membrane - 40 mil (48")	varies/size	48" x 75' roll	25 ctns/pallet	76#/ctn
Polyguard 650 LT Liquid Adhesive or Shur-Tac Liquid Adhesive are not required as a primer when 300 or 400 Membranes are applied over cured Airlok Flex® VP.				
Quick Grip Spray Adhesive	PWQGADH30	30# canister covers approximately 1000 SF		